

Easy, safe and simple seal featuring low running cost.



Shape of sealing

# Ultrasonic point sealer

Ultrasonic point sealing for plastic materials  
QP-01

An alternative to;



Tape



Stapler



Rubber band



Glue

This machine has various uses.



Able to weld food packs and fit containers without using a stapler or tape. Consumables such as staples are not used, and therefore, this sealer can prevent foreign matters from entering.

## Example of use

For food packs, fit packs, plastic bags, blister bags, basting, etc.



Food pack



Snap-on pack



Plastic bag



Basting



Blister pack



Food net

# Ultrasonic sealer


E A S Y X S A F E


## Ultrasonic point sealing


Just press the hand-piece lightly  
The hand piece generates ultrasonic waves  
and weld by heat in two seconds or less.



### Operating Instruction


- 

Turn on the power switch of the main unit
- 

Turn the timer knob to adjust the welding time
- 

Easily welds by inserting packaging in the handset and lightly pressing it together.

### - Handpiece



Oscillation horn  
Lower tip



### Food safety

Consumables such as needles are not used, and therefore, this ultrasonic point sealer can prevent foreign matter from entering and provide attractive packing appearance.

### Easy to use

The hand-piece generates ultrasonic waves and spot welds by heat in two seconds or less.

### Added level of safety

QP-01 can be used to create a type of tamper proof seal easily at low cost, and can also seal any plastic containers that you may already have. You can be more confident that your snap-on and clam shell packages will be securely and reliably sealed.

### - Easy to see contact points

The work efficiency can be improved.

### Specifications

Product name	Ultrasonic point sealer
Model	QP-01
Oscillation frequency	57kHz
Output	20W
Power source	100V-240V AC50/60Hz
Main unit	W179×D183×H66mm / 1000g
Handpiece	W36×D125×H54mm / 200g
Length of coiled cord	50cm
Power cord length	AC side 1.8m, DC side 1.5m

### Compatible sealing material

		For upper side						
		PSP	OPS	PVC	HIPS	PPF	PP	A-PET
For lower side	PSP	○	○	△	○	×	×	○
	OPS	○	○	△	○	○	○	○
	PVC	×	×	△	△	×	△	△
	HIPS	○	○	×	○	×	×	○
	PPF	×	×	×	×	○	○	×
	PP	×	×	×	×	○	○	×
	A-PET	×	×	△	○	○	○	○

### Movie



\*Specifications and appearance are subject to change without notice for improvement.

## C.V. POLYPACK PERKASA

DUTA HARAPAN INDAH BLK JJ No. 31  
JLN. KAPUK MUARA, JAKARTA - 14460, INDONESIA  
Telp : +6221-6682594, 6622508, Fax : +6221-66694052  
Email : sales@cvpolypackperkasa.com  
Website : www.cvpolyackperkasa.com

