



SF TOOLS™

SHRINKFAST 200

SHRINKFAST 200™

SERIOUS FIREPOWER
FOR SERIOUS PROFESSIONALS

The Shrinkfast 200™ (originally known as the Shrinkfast 998) is the premier professional-grade direct heat tool on the market. Its 200,000+ BTUs of power and unprecedented safety features protect both your team and your assets. The Shrinkfast 200™ is the direct heat tool of choice for serious professionals around the world.

Proudly designed and manufactured in the U.S.A.



DESIGNED FOR SAFETY

- UL, ULC and CE Safety Certified
- “Dead-man” trigger automatically shuts off propane flow and extinguishes flame when released
- Patented ignition system allows for reliable firing of heat tool every time
- The combustor remains cool to the touch during operation
- UL-approved regulator assembly features an “Excess Flow Device” that stops the flow of propane if hose is cut
- Tested for peak performance and safety before shipping

POWERFUL & PRECISE

- Generates 200,000 BTUs of power
- Wraps standard 40" x 48" x 60" pallets in less than 2 minutes
- Fan-shaped combustor creates an even, steady fan pattern for consistent heat distribution
- Adjustable BTU output for a variety of applications

LIGHTWEIGHT & DURABLE

- Lightweight design (2.2 lbs.) for easy maneuverability
- Combines rugged glass-filled polycarbonate housing with a comfortable ergonomic grip
- Heavy duty UL-approved 25' hose withstands up to 300 lbs of pressure
- One-year manufacturer's warranty on parts and labor
- Full-service repair facility located in Newport, New Hampshire

VERSATILE & EASY TO USE

- Designed for quick, easy assembly – operational in less than 5 minutes
- Quick disconnect system for easy installation of accessories and extensions
- Integrated extension system and X-Tender for hard-to-reach areas and oversized applications
- SF Tools™ offers several personal protective equipment (PPE) accessories
- Contact SF Tools™ directly if you have questions

SHRINKFAST **200**™

POWER AT 27 PSI	187,000 BTUs
TOOL WEIGHT	2.2 lbs
TOOL LENGTH	14"
COMPLETE KIT WEIGHT	13 lbs
RATED CAPACITY @ 27 PSI	55 KW
RECOMMENDED PRESSURE RANGE	20 - 30 PSI
TEMPERATURE - 6" FROM FLAME	1,200° F
FUEL CONSUMPTION (LBS/HR)	8.65 lbs / hour
AIR CONSUMPTION	30 CFM
CO2 EMISSION	2.8% CO2
CO EMISSION	91 PPM CO
NOISE LEVEL	88 dbA
ENERGY SOURCE	Propane or Natural Gas
UL, ULC & CE CERTIFIED	Yes
MADE IN THE U.S.A.	Manufactured in Newport, NH

GET THE JOB DONE RIGHT



PACKAGING & TRANSPORTATION

Shrink wrap large and oddly shaped objects faster.



CONSTRUCTION

Powerful and durable for direct heat applications on big job sites.



MARINE STORAGE

Protects boats from the elements for seasonal storage.

ACCESSORIES

SF Tools™ are designed for versatility. Outfit your heat tool with professional-grade accessories made to optimize performance for a variety of tasks.



2, 4 AND 6 FT EXTENSIONS



SAFETY GLOVES